

Han 3A-HBMA-SL-red



Image is for illustration purposes only. Please refer to product description.

Part number	09 20 003 0804
Specification	Han 3A-HBMA-SL-red
HARTING eCatalogue	https://b2b.harting.com/09200030804

Identification

Category	Hoods/Housings
Series of hoods/housings	Han A [®]
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	Angled

Version

Size	3 A
Locking type	Single locking lever
Field of application	Standard Hoods/housings for industrial applications

Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP44 IP65 / IP67 with seal screw 09 20 000 9918
Type rating acc. to UL 50 / UL 50E	12

Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	Red
Material (seal)	NBR
Material (locking)	Steel



Pushing Performance
Since 1945

Material properties

Surface (locking)	Zinc plated
-------------------	-------------

Specifications and approvals

Approvals	DNV GL
CE	Yes

Commercial data

Packaging size	10
Net weight	63 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140279247
eCl@ss	27440202 Shell for industrial connectors
