

## D-Sub HD 78-pole female crimp contacts



Image is for illustration purposes only. Please refer to product description.

Part number	09 56 500 4701
Specification	D-Sub HD 78-pole female crimp contacts
HARTING eCatalogue	<a href="https://b2b.harting.com/09565004701">https://b2b.harting.com/09565004701</a>

### Version

Termination method	Crimp termination
Gender	Female
Size	D-Sub 5
Number of contacts	78
Locking type	Fixing flange with feed through hole $\varnothing$ 3.1 mm

### Technical characteristics

Conductor cross-section	0.14 ... 0.25 mm <sup>2</sup>
Conductor cross-section	AWG 26 ... AWG 24
Wire outer diameter	$\leq$ 1.38 mm
Clearance distance	$\geq$ 1 mm
Creepage distance	$\geq$ 1 mm
Insulation resistance	$> 5 \times 10^9 \Omega$
Limiting temperature	-40 ... +85 °C
Test voltage $U_{r.m.s.}$	1 kV
Isolation group	IIIa ( $175 \leq CTI < 400$ )
Hot plugging	No

### Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled (PBTP) Shell: steel, nickel plated
Colour (insert)	Black
Material (contacts)	Copper alloy



**Pushing Performance**  
Since 1945

## Material properties

Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead
Requirement set with Hazard Levels	R26

## Specifications and approvals

Specifications	DIN 41652
UL / CSA	UL 1977 ECBT2.E102079

## Commercial data

Packaging size	50
Net weight	15.48 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140072220
eCl@ss	27440214 D-Sub coupler