

## D SUB HD FE 78P SOLDER CUP PL3



Image is for illustration purposes only. Please refer to product description.

Part number	09 56 500 4704
Specification	D SUB HD FE 78P SOLDER CUP PL3
HARTING eCatalogue	<a href="https://b2b.harting.com/09565004704">https://b2b.harting.com/09565004704</a>

### Version

Termination method	Solder cup termination
Gender	Female
Size	D-Sub 5
Number of contacts	78
Locking type	Fixing flange with feed through hole $\varnothing$ 3.1 mm

### Technical characteristics

Conductor cross-section	0.25 mm <sup>2</sup>
Conductor cross-section	AWG 24
Rated current	2 A
Clearance distance	$\geq$ 1 mm
Creepage distance	$\geq$ 1 mm
Insulation resistance	$> 5 \times 10^9 \Omega$
Contact resistance	$<$ 20 m $\Omega$
Limiting temperature	-40 ... +85 °C
Performance level	3
Mating cycles	$\geq$ 50
Test voltage $U_{r.m.s.}$	1 kV
Isolation group	IIIa ( $175 \leq CTI < 400$ )
Hot plugging	No



Pushing Performance  
Since 1945

## Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled (PBTP) Shell: steel, nickel plated
Colour (insert)	Black
Material (contacts)	Copper alloy
Surface (contacts)	Noble metal over Ni Mating side Sn over Ni Termination side
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Requirement set with Hazard Levels	R26

## Specifications and approvals

Specifications	DIN 41652
UL / CSA	UL 1977 ECBT2.E102079

## Commercial data

Packaging size	50
Net weight	18.92 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140072237
eCl@ss	27440214 D-Sub coupler