

UIC558-22PIN-MI-CRT



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 58 022 3001 |
| Specification | UIC558-22PIN-MI-CRT |
| HARTING eCatalogue | https://b2b.harting.com/09580223001 |

Identification

| | |
|----------|-----------------|
| Category | Inserts |
| Series | HARTING UIC 558 |

Version

| | |
|--------------------|---|
| Termination method | Crimp termination |
| Gender | Male |
| Number of contacts | 22 |
| PE contact | Yes |
| Details | Please order crimp contacts separately. |

Technical characteristics

| | |
|-------------------------|----------------------------|
| Conductor cross-section | 0.75 ... 1 mm ² |
| Conductor cross-section | AWG 18 ... AWG 17 |
| Rated current | 10 A |
| Rated voltage | 60 V |
| Insulation resistance | >10 ⁷ Ω |
| Limiting temperature | -50 ... +125 °C |
| Mating cycles | ≥10,000 |

Material properties

| | |
|-------------------|----------------|
| Material (insert) | Polyamide (PA) |
| Colour (insert) | Black |



Pushing Performance
Since 1945

Material properties

| | |
|---|-----|
| Material flammability class acc. to UL 94 | V-0 |
|---|-----|

Specifications and approvals

| | |
|----------------|----------------------|
| Specifications | UIC 550 |
| | IRS 50558 |
| | IEC 61373 Category 2 |
| | IEC 60529 |

Commercial data

| | |
|--------------------------------|---|
| Packaging size | 1 |
| Net weight | 35 g |
| Country of origin | India |
| European customs tariff number | 85389099 |
| GTIN | 5713140187009 |
| eCl@ss | 27440205 Contact insert for industrial connectors |