

## Han 3EMC-HBM-SL stainless steel lever



Image is for illustration purposes only. Please refer to product description.

Part number	09 62 003 0305
Specification	Han 3EMC-HBM-SL stainless steel lever
HARTING eCatalogue	<a href="https://b2b.harting.com/09620030305">https://b2b.harting.com/09620030305</a>

### Version

Size	3 A
Locking type	Single locking lever
Field of application	Hoods/Housings for higher EMC requirements

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP44 IP65 / IP67 with seal screw 09 20 000 9918
Type rating acc. to UL 50 / UL 50E	12

### Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Uncoated
Colour (hood/housing)	Unpainted
Material (seal)	NBR
Material (locking)	Stainless steel
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained



**Pushing Performance**  
Since 1945

## Material properties

California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

CE	Yes
Approvals	DNV GL

## Commercial data

Packaging size	10
Net weight	32 g
Country of origin	Romania
European customs tariff number	85389099
GTIN	5713140073029
eCl@ss	27440202 Shell for industrial connectors