

Han® S 200 FC CRT 25 mm² w. rubb. sleeve



Image is for illustration purposes only. Please refer to product description.

Part number	09 93 000 6262
Specification	Han® S 200 FC CRT 25 mm ² w. rubb. sleeve
HARTING eCatalogue	https://b2b.harting.com/09930006262

Version

Manufacturing process	Turned contacts
-----------------------	-----------------

Technical characteristics

Conductor cross-section	25 mm ²
Conductor cross-section	AWG 4
Operating current	≤200 A
Contact resistance	≤0.3 mΩ
Stripping length	22 mm

Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (accessories)	Thermoplastic polyurethane (TPU)
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained



Pushing Performance
Since 1945

Specifications and approvals

Specifications	IEC 60664-1
	IEC 61984

Commercial data

Packaging size	1
Net weight	41.9 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140188785
eCl@ss	27440204 Contact for industrial connectors