

## Han-Eco 16A-Cover



Image is for illustration purposes only. Please refer to product description.

Part number	19 46 016 5425
Specification	Han-Eco 16A-Cover
HARTING eCatalogue	<a href="https://b2b.harting.com/19460165425">https://b2b.harting.com/19460165425</a>

### Identification

Category	Accessories
Series of hoods/housings	Han-Eco® A
Type of hood/housing	Protection cover
Description of hood/housing	for bulkhead mounted housings for surface mounted housings

### Version

Size	16 A
Locking type	Single locking lever

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Number of relockings	≥500
Degree of protection acc. to IEC 60529	IP65

### Material properties

Material (hood/housing)	Polyamide (PA) Fibre-glass reinforced
Colour (hood/housing)	RAL 9005 (jet black)
Material (seal)	NBR
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e



**Pushing Performance**  
Since 1945

## Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

## Specifications and approvals

Specifications	IEC 61984 EN 45545-2 Fire protection on railway vehicles
----------------	---

## Commercial data

Packaging size	1
Net weight	29.4 g
Country of origin	Germany
European customs tariff number	39269097
GTIN	5713140192188
eCl@ss	27440208 Cap for industrial connectors