

## Han 16EMC/B-HTE2/HSE-M20/M32 (HT)



Image is for illustration purposes only. Please refer to product description.

Part number	19 62 816 0529
Specification	Han 16EMC/B-HTE2/HSE-M20/M32 (HT)
HARTING eCatalogue	<a href="https://b2b.harting.com/19628160529">https://b2b.harting.com/19628160529</a>

### Version

Size	16 B
Version	Top/side entry
Cable entry	2x M20 1x M32
Locking type	Double locking lever
Field of application	Hoods/Housings for higher EMC requirements

### Technical characteristics

Limiting temperature	-40 ... +125 °C -40 ... +200 °C With Han® High Temp components
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65 IP66
Type rating acc. to UL 50 / UL 50E	4 12

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Uncoated
Colour (hood/housing)	Unpainted
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained



**Pushing Performance**  
Since 1945

## Material properties

REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes

## Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes
Approvals	DNV GL

## Commercial data

Packaging size	1
Net weight	200 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140171909
eCl@ss	27440202 Shell for industrial connectors