

DIN 41626 male connector 1mm POF



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 20 10 001 4211 |
| Specification | DIN 41626 male connector 1mm POF |
| HARTING eCatalogue | https://b2b.harting.com/20100014211 |

Identification

| | |
|----------------------------|------------------------|
| Category | Contacts |
| Series | DIN 41626 |
| Type of contact | FO contact |
| Description of the contact | for 1 mm plastic fibre |

Version

| | |
|-----------------------|-----------------|
| Gender | Male |
| Manufacturing process | Turned contacts |

Material properties

| | |
|--------------------------------------|--|
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | b51e5b97-eeb5-438b-8538-f1771d43c17d |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |



Pushing Performance
Since 1945

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 10 |
| Net weight | 1.7 g |
| Country of origin | Germany |
| European customs tariff number | 85367000 |
| GTIN | 5713140133372 |
| eCl@ss | 27440204 Contact for industrial connectors |